

TEX

Denomination: **HIGH PERFORMANCE WOOD SCREW**

Codes: **TEXBT, TEXBP, TECBT, TEXZT, TEXZP, TEXAB**

Reference: **FT TEX-en**

Date: **13/07/18**

Revision: **5**

Page: **5 of 12**

2.3 TEC-BT

Yellow zinc-plated wide head wood screw Tx recess



MATERIALS & GEOMETRY



Steel

Yellow
Zinc-Plated

Tx

Serrated
S Tip

CHARACTERISTICS

- Yellow zinc-plated coating
- Wide head and y S tip.
- Tx recess
- Application: Fixing ironwork to wood, joining wood structures to each other, fixing reinforcing metal joints to wood, load-bearing wood structures.

BENEFITS



CE Marking

Installation with screwdriver

DIAMETER

Ø 6.0

Ø 8.0

Ø 10.0

dk: head diameter

[mm]

14.5

21.5

25.5

k: head height

[mm]

3.1

3.7

4.1

L: lengths

[mm]

80 – 200

80 – 300

100 – 300

D: external thread diameter

[mm]

6.0

8.0

10.0

d: inside thread diameter

[mm]

3.9

5.6

6.5

p: thread pitch

[mm]

4.6

6.2

6.8

Tx recess

T30

T40

T40

Installation bit code

PUTO30

PUTO40

PUTO40

