

TEX

Denomination: **HIGH PERFORMANCE WOOD SCREW**

Codes: **TEXBT, TEXBP, TECBT, TEXZT, TEXZP, TEXAB**

Reference: **FT TEX-en**

Date: **13/07/18**

Revision: **5**

Page: **4 of 12**

2.2 TEX-BP

Yellow zinc-plated wood screw Pz recess



MATERIALS & GEOMETRY



Steel

Yellow zinc-plated

Pz

Serrated S Tip

CHARACTERISTICS

- Yellow zinc-plated coating
- Countersunk head and y S tip.
- Pz recess
- Application: Fixing ironwork to wood, joining wood structures to each other, fixing reinforcing metal joints to wood, load-bearing wood structures.

BENEFITS



CE Marking

Patent

Installation with screwdriver

DIAMETER		Ø 2.5	Ø 3.0	Ø 3.5	Ø 4.0	Ø 4.5	Ø 5.0	Ø 6.0
dk: head diameter	[mm]	5.00	6.00	7.00	8.00	8.80	9.80	11.80
L: lengths	[mm]	10 - 25	10 - 45	10 - 50	12 - 80	16 - 80	25 - 120	40 - 120
D: external thread diameter	[mm]	2.5	3.0	3.5	4.0	4.5	5.0	6.0
d: inside thread diameter	[mm]	1.6	2.0	2.3	2.6	2.9	3.3	3.9
p: thread pitch	[mm]	1.3	1.60	2.00	2.30	3.6	4.0	4.6
Pz recess			PZ1	PZ2	PZ2	PZ2	PZ2	PZ3
Installation bit code			PUPOC01 PUPOL01	PUPOC02 PUPOL02	PUPOC02 PUPOL02	PUPOC02 PUPOL02	PUPOC02 PUPOL02	PUPOC03 PUPOL03

