

2.6 AB-IR

Isophonic pipe clamp M8 fast-clip



Benefits



Coating



Zinc-plated

Base Material



Steel pipe

Copper pipe

PVC pipe

Installation data

Code	Size [mm]	Ø D (mm)	Ø D (")	A x B (mm)	Maximum load recommended (kg)	Characteristics
ABIR015	16	14 - 15	1/4"	19x1,2	60	<ul style="list-style-type: none"> <li>• Pipes from Ø16 to Ø60 mm.</li> <li>• Surface coating: electrolytic zinc plated, coating &gt;5 microns.</li> <li>• Vertical opening allowing quick installation.</li> <li>• Only one screw included.</li> <li>• Isophonic, EPDM rubber for insulation, noise and vibration reduction.</li> <li>• Welded nut M8.</li> <li>• According to Technical Building Code, TBC, Basic reports HS and HR.</li> <li>• Steel profile of 1.5 mm thickness.</li> <li>• Recommended for water supply installations (HSW and CW), drain networks (sanitation), thermal installations (heating, air-conditioning and ventilation systems), compressed air, gas installations, etc.</li> <li>• Service temperature: -30°C ÷ +120°C.</li> <li>• Easy, economic and quick installation</li> </ul>
ABIR018	18	16 - 19	3/8"	19x1,2	60	
ABIR022	22	21 - 23	1/2"	19x1,2	60	
ABIR028	28	26 - 28	3/4"	19x1,2	60	
ABIR035	35	32 - 35	1"	19x1,2	60	
ABIR040	42	40 - 43	1 1/4"	19x1,2	60	
ABIR048	48	48 - 51	1 1/2"	19x1,2	60	
ABIR054	54	52 - 56	-	19x1,2	60	
ABIR060	60	57 - 60	2"	19x1,2	60	

DRAWING

