

2.10 AB- RID

Isophonic heavy-duty sliding clamp M8 + M10



Benefits



Coating



Zinc-plated

Base Material



Steel pipe



Copper pipe



PVC pipe

Installation Data

Code	Ø D (mm)	A x B (mm)	C	Fixing range D (mm)	Maximum load recommended (kg)	Characteristics
ABRID016	16	20 x 1,2	17	16 - 19	150	- Pipes from Ø16 to Ø160 mm. - Surface coating: electrolytic zinc plated, coating >3 microns. - Isophonic, EPDM rubber for insulation, noise and vibration reduction. - Steel profile de 1,2 ÷ 2,0 mm thickness. - Side screws with plastic washer to avoid losses. - Specially indicated for PVC pipes - Welded nut of M8+M10. - Suitable for steel, plastic, copper and ventilation pipes. - Easy and fast installation.
ABRID020	20	20 x 1,2	17	20 - 23	150	
ABRID025	25	20 x 1,2	17	25 - 30	150	
ABRID032	32	20 x 1,2	17	31 - 36	150	
ABRID040	40	20 x 1,2	17	40 - 46	150	
ABRID050	50	20 x 1,5	17	48 - 53	150	
ABRID063	63	20 x 1,5	17	60 - 65	150	
ABRID075	75	20 x 1,5	17	72 - 78	150	
ABRID090	90	20 x 1,5	17	87 - 92	150	
ABRID110	110	20 x 2,0	17	105 - 115	150	
ABRID125	125	20 x 2,0	17	124 - 130	150	
ABRID140	140	20 x 2,0	17	135 - 145	150	
ABRID160	160	20 x 2,0	17	160 - 168	150	

DRAWING

